

## Silicon Field Stop(FS) Planar IGBT


### Description

The THG75N120FQL is use advanced field stop(FS) technology.

The 1200V FS IGBT offers superior conduction and switching performances.

### General Features

- 1200V Breakdown Voltage
- Low saturation voltage: $V_{CE(sat)}$ , typ=2.3V@ $I_C=75A$
- FS Planar Technology, Positive temperature coefficient
- High speed switch & Low power loss



### Application

- Solar Converters
- Welding Converters
- UPS

### Product Summary

|               |       |
|---------------|-------|
| $V_{CE}$      | 1200V |
| $V_{CE(sat)}$ | 2.3V  |
| $I_C$         | 75A   |

### MAXIMUM RATINGS ( $T_J = 25^\circ C$ unless otherwise noted)

| Parameter                    | Symbol   | Value             | Unit |   |
|------------------------------|----------|-------------------|------|---|
| Collector-to-Emitter Voltage | $V_{CE}$ | 1200              | V    |   |
| Gate-to-Emitter Voltage      | $V_{GE}$ | $\pm 30$          | V    |   |
| Collector Current            | $I_C$    | $T_C=25^\circ C$  | 150  | A |
|                              |          | $T_C=100^\circ C$ | 75   |   |
| Power Dissipation            | $P_D$    | $T_C=25^\circ C$  | 789  | W |
|                              |          | $T_C=100^\circ C$ | 394  |   |

|  |  |                |                      |                    |
|--|--|----------------|----------------------|--------------------|
| Pulsed Collector Current   | $T_C=25^{\circ}\text{C}$<br>$t_p=10\mu\text{s}$ (Note 1) | $I_{CM}$       | 225                  | A                  |
| Diode Forward Current  | $T_C=25^{\circ}\text{C}$                                 | $I_F$          | 150                  |                    |
|  | $T_C=100^{\circ}\text{C}$                                |                | 75                   |                    |
| Pulsed Diode Forward Current   | $T_C=25^{\circ}\text{C}$<br>$t_p=10\mu\text{s}$ (Note 1) | $I_{FM}$       | 225                  |                    |
| Short Circuit Withstand Time<br>$V_{GE} = 15\text{ V}, V_{CC} = 800\text{ V}, T_C = 150^{\circ}\text{C}$ |  | $T_{SC}$       | 10                   | $\mu\text{s}$      |
| Operating Junction and Storage Temperature Range   |  | $T_J, T_{stg}$ | -55<br>$T_o$<br>+175 | $^{\circ}\text{C}$ |
| Lead Temperature for Soldering Purposes  |  | $T_L$          | 270                  |                    |

### THERMAL CHARACTERISTICS

| Parameter                                     | Symbol     | Value | Unit                        |
|---|------------|-------|-----------------------------|
| Thermal Resistance, Junction-to-Case for IGBT | $R_{thJC}$ | 0.19  | $^{\circ}\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Ambient       | $R_{thJA}$ | 62.5  |                             |

### ELECTRICAL CHARACTERISTICS ( $T_J = 25^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Value |      |      | Unit | Test Condition |
|-----------|--------|-------|------|------|------|----------------|
|           |        | min.  | typ. | max. |      |                |

#### OFF CHARACTERISTICS

|  |            |      |   |           |               |   |
|--|------------|------|---|-----------|---------------|---|
| Collector-to-Emitter Breakdown Voltage | $BV_{CES}$ | 1200 | - | -         | V             | $V_{GE}=0\text{V}, I_C=1\text{mA}$        |
| Zero Gate Voltage Collector Current    | $I_{CES}$  | -    | - | 40        | $\mu\text{A}$ | $V_{GE}=0\text{V}, V_{CE}=V_{CES}$        |
| Gate-to-Emitter leakage Current        | $I_{GES}$  | -    | - | $\pm 400$ | nA            | $V_{GE}=\pm 30\text{V}, V_{CE}=0\text{V}$ |

#### ON CHARACTERISTICS

|   |               |     |     |     |   |   |
|---|---------------|-----|-----|-----|---|---|
| Gate-to-Emitter Threshold Voltage       | $V_{GE(th)}$  | 4.8 | -   | 6.6 | V | $V_{GE}=V_{CE}, I_C=1\text{mA}, T_J=25^{\circ}\text{C}$     |
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | -   | 2.3 | 2.8 | V | $V_{GE}=15\text{V}, I_C=75\text{A}, T_J=25^{\circ}\text{C}$ |

**DYNAMIC CHARACTERISTICS**

|                              |           |   |      |   |    |   |
|------------------------------|-----------|---|------|---|----|---|
| Input Capacitance            | $C_{IES}$ | - | 6221 | - | pF | $V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V},$<br>$f = 1\text{ MHz}$    |
| Output Capacitance           | $C_{OES}$ | - | 433  | - |    |   |
| Reverse Transfer Capacitance | $C_{RES}$ | - | 140  | - |    |   |
| Total Gate Charge            | $Q_G$     | - | 310  | - | nC | $V_{CE} = 600\text{ V}, V_{GE} = 15\text{ V},$<br>$I_C = 75\text{ A}$ |

**SWITCHING CHARACTERISTICS**

|                         |              |   |      |   |    |  |
|-------------------------|--------------|---|------|---|----|--|
| Turn-On Delay Time      | $t_{d(on)}$  | - | 202  | - | ns | $V_{CE} = 600\text{ V}$<br>$V_{GE} = 0/15\text{ V}$<br>$I_C = 75\text{ A}$<br>$R_G = 30\ \Omega$<br>$T_J = 25^\circ\text{C}$ |
| Turn-Off Delay Time     | $t_{d(off)}$ | - | 398  | - |    |  |
| Rise time               | $t_r$        | - | 42   | - |    |  |
| Fall time               | $t_f$        | - | 155  | - |    |  |
| Turn-On Switching Loss  | $E_{on}$     | - | 11   | - | mJ |  |
| Turn-Off Switching Loss | $E_{off}$    | - | 3.9  | - |    |  |
| Total Switching Loss    | $E_{ts}$     | - | 14.9 | - |    |  |

**ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise specified) (continued)

| Parameter | Symbol | Value |      |      | Unit | Test Condition |
|-----------|--------|-------|------|------|------|----------------|
|           |        | min.  | typ. | max. |      |                |

**SWITCHING CHARACTERISTICS**
**DIODE CHARACTERISTICS**

|                       |       |   |     |     |   |   |
|-----------------------|-------|---|-----|-----|---|---|
| Diode Forward Voltage | $V_F$ | - | 2.2 | 3.3 | - | $I_F = 75\text{ A}, T_J = 25^\circ\text{C}$ |
|-----------------------|-------|---|-----|-----|---|---|

**DIODE SWITCHING CHARACTERISTICS, INDUCTIVE LOAD**

|                               |           |   |      |   |    |  |
|-------------------------------|-----------|---|------|---|----|--|
| Reverse Recovery Time         | $t_{rr}$  | - | 45   | - | ns | $V_R = 600\text{ V}, I_F = 75\text{ A},$<br>$dI_F/dt = 200\text{ A}/\mu\text{s}$<br>$T_J = 25^\circ\text{C}$ |
| Reverse Recovery Charge       | $Q_{rr}$  | - | 1300 | - | nC |  |
| Reverse Recovery Energy       | $E_{rec}$ | - | 0.18 | - | mJ |  |
| Peak Reverse Recovery Current | $I_{RRM}$ | - | 45   | - | A  |  |

### Typical Performance Characteristics




Figure 1. Typical Output Characteristics IGBT




Figure 2. Typical Output Characteristics IGBT




Figure 3. Typical Transfer characteristics IGBT




Figure 4. Switching Energy vs Gate Resistor IGBT




Figure 5. Switching Energy vs Collector Current IGBT




Figure 6. Reverse Biased Safe Operating Area IGBT




Figure 7. Collector Current vs Case temperature IGBT




Figure 8. Forward current vs Case temperature Diode




Figure 9. Diode Forward Characteristics Diode




Figure 10. Switching Energy vs Gate Resistor Diode




Figure 11. Switching Energy vs Forward Current Diode





Figure 12. Transient Thermal Impedance of Diode and IGBT

## Package Information

### TO-264 PACKAGE

#### 基本尺寸



| Symbol   | 单位 mm |      |      |
|----------|-------|------|------|
|          | Min   | Nom  | Max  |
| A        | 4.80  | 5.00 | 5.20 |
| A1       | 1.80  | 2.00 | 2.20 |
| A2       | 3.20  | 3.40 | 3.60 |
| b        | 0.80  | 1.00 | 1.20 |
| b1       | 2.90  | 3.10 | 3.30 |
| b2       | 2.40  | 2.60 | 2.80 |
| c        | 0.50  | 0.60 | 0.70 |
| e        | 5.25  | 5.45 | 5.65 |
| E        | 19.8  | 20.0 | 20.2 |
| E1       | 17.6  | 17.8 | 18.0 |
| E2       | 8.60  | 8.80 | 9.00 |
| H        | 25.8  | 26.0 | 26.2 |
| H1       | 19.8  | 20.0 | 20.2 |
| H2       | 19.8  | 20.3 | 20.8 |
| H3       | 2.00  | 2.50 | 3.00 |
| G        | 6.00  | 6.20 | 6.40 |
| $\Phi P$ | 3.00  | 3.20 | 3.40 |
| J        | 4.80  | 5.00 | 5.20 |
| K        | 1.30  | 1.50 | 1.70 |

## Notice

Thunder Microelectronics Incorporated Limited reserves the right to make changes without further notice to any products or specifications herein. When use the product, be sure to obtain the latest specification.

Thunder Microelectronics Incorporated Limited does not assume any liability arising out of the application or any product described herein. When using Thunder Microelectronics Incorporated Limited products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury ,fire or other problem if any of the products become faulty.

### -Headquarters

WuXi Thunder Microelectronics Incorporated Limited

Building E1-901, No.200 LingHu Road, XinWu district,WuXi,China 214135

Tel:+86-510-85160109

Fax:+86-510-85160109